



PVC FIBRE REINFORCED HOSE



TUBE:

- PVC

REINFORCEMENT:

- High Tensile Polyester

TEMP RANGE:

- -10°C to + 70°C Approx

APPLICATIONS:

- Conveying Water, Oil, Gas Under Normal Working Condition In The Factory, Farm, Ship, Building And Family
- Conveying Milk, Beverages and Other Foods.
- Used in PVC Shower Hose.

FEATURES:

- Flexible, Transparent, Durable, Non-Toxic & Odorless
- Anti-Erosion and Anti-Abrasion
- Adding Colorful Symbol Lines on the Surface of the hose.
- Food Grade Material

PVC FLEXIBLE INDUSTRIAL AND COMMERCIAL HOSE

SIZE (MM)	SIZE (INCH)	WHITE BRAIDED (APPROX WEIGHT) PENGUIN (KG)	APEX (KG)	LENGTH (MTRS)
6	1/4"	10 - 11	9 - 10	100
8	5/16"	12 - 13	11 - 12	100
10	3/8"	15 - 16	14 - 15	100
12.5	1/2"	18 - 19	15 - 16	100
16	5/8"	12 - 13	9 - 10	50
20	3/4"	16 - 17	14 - 15	50
25	1"	21 - 22	18 - 19	50
32	1 1/4"	16 - 17	16 - 17	30
38	1 1/2"	21 - 22	21 - 22	30
50	2"	32 - 33	32 - 33	30

PVC FLEXIBLE MULTIPURPOSE HOSE

SIZE (MM)	SIZE (INCH)	COLOR BRAIDED (APPROX WEIGHT) (KG)	LENGTH (MTRS)
12.5	1/2"	3.5	30
16	5/8"	4.5	30
19	3/4"	5.5	30
25	1"	8.1 - 8.4	30
32	1 1/4"	14 - 15	30

FACTORY

B - 29/4, M.I.D.C. Taloja,
Near Pendhar Village,
Navi Mumbai - 410 208,
Dist. Raigad, Maharashtra, INDIA.
☎ +91 96190 05887

✉ info@akshayplastics.in

🌐 www.akshayplastics.in

CA. Tejash Vakharia

☎ +91 98210 17637

✉ tejashvakharia@yahoo.com

Vinit Vakharia

☎ +91 98216 18366

✉ vinit_vakharia@rediffmail.com